



Safety Data Sheet

Product Name: E-Color/GH Combo Buffing Wheels

Revision Date: February 22, 2016

Issue Date: May 3, 2005

1. Product and Company Identification

Product Name: E-Color/GH Combo Buff

Product Description: Cotton Buffing Wheel
(All sizes)

Company Address:

Schaffner Manufacturing Co. Inc.
21 Herron Ave.
Emsworth, PA 15202

Contact Information:

Telephone: 412-761-9902
Emergency Telephone: 412-761-9902
Internet: www.schaffnermfg.com

2. Hazards Identification

Signal Word: Warning

Primary Entry Routes: Skin contact, eye contact

Target Organs: Skin, eyes

Acute Effects

Inhalation: Irritation possible from prolonged contact

Eye: Irritation possible from prolonged contact

Skin: Irritation possible from prolonged contact

Ingestion:

Carcinogenicity: IARC, NTP, and OSHA do not list this product as carcinogenic

Medical Conditions Aggravated by Long-Term Exposure: N/A

Chronic Effects: N/A

3. Composition - Information on Ingredients

Ingredient Name	CAS Number
Cotton Fabric	N/A

Ingredient	OSHA PEL		ACGIH TLV		NIOSH REL		NIOSH IDLH
	TWA	STEL	TWA	STEL	TWA	STEL	
Cotton Fabric	none estab.	none estab.	none estab.	none estab.	none estab.	none estab.	none estab.



Safety Data Sheet

Product Name: E-Color/GH Combo Buffing Wheels

Revision Date: February 22, 2016

Issue Date: May 3, 2005

4. First Aid Measures

Emergency and First Aid Procedures

Inhalation: Cough to clear throat. Seek Medical Attention

Eye Contact: Rinse with water for 15 minutes. Seek medical attention.

Skin Contact: Rinse with water.

Ingestion: Give water. Seek Medical attention.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Note to Physicians: None

Special Precautions/Procedures: It is recommended that safety glasses and dust mask be worn during operation

5. Fire Fighting Measures

Flash Point: Unknown - Cotton Yellows at 250 ° F

Flash Point Method: N/A

Burning Rate: N/A

Autoignition Temperature: N/A

LEL: N/A

UEL: N/A

Flammability Classification: N/A

Extinguishing Media: Water, carbon dioxide, and foam

Unusual Fire or Explosion Hazards: Cotton Dust or lint is very flammable.

Hazardous Combustion Products: N/A

Fire-Fighting Instructions: Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.

Hazard Classification: Health: **1** Flammability: **1** Reactivity: **0**



0 = Minimal 1=Slight 2=Moderate 3=Serious 4=Severe

6. Accidental Release Measures

Environmental Precautions: No special precautions required, disposal must be made in accordance with Federal, State and Local regulations.

Clean-up Methods: Vacuum or sweep spilled material and place waste material in approved container.



Safety Data Sheet

Product Name: E-Color/GH Combo Buffing Wheels

Revision Date: February 22, 2016

Issue Date: May 3, 2005

7. Handling and Storage

Handling: Protective gloves are recommended for prolonged handling.

Storage: Store in a cool, dry area.

Incompatible Products: Glycerol, Oxygen DiFlouride and strong oxidizers.

8. Exposure Controls/ Personal Protection

Engineering Controls:

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Administrative Controls:

Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Protective Clothing/Equipment: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Safety Stations: Make emergency eyewash stations and washing facilities available in work area.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.



Safety Data Sheet

Product Name: E-Color/GH Combo Buffing Wheels

Revision Date: February 22, 2016

Issue Date: May 3, 2005

9. Physical and Chemical Properties

Physical State: Solid
Appearance and Odor: Aqua/White
Odor Threshold: N/A
Vapor Pressure: N/A
Vapor Density (Air=1): N/A
Formula Weight: none estab.
Density: N/A
Specific Gravity (H₂O=1, at 4 °C): N/A
pH: N/A

Water Solubility: N/A
Other Solubilities: N/A
Boiling Point: N/A
Freezing/Melting Point: N/A
Viscosity: N/A
Refractive Index: N/A
Surface Tension: N/A
% Volatile: N/A
Evaporation Rate: N/A

10. Stability and Reactivity

Stability: All Schaffner products are stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: N/A

Conditions to Avoid: N/A

Hazardous Decomposition Products: If involved in a fire, treated buffing wheels may release small amounts of Carbon Monoxide due to incomplete combustion of the treatment. This product will not release carbon monoxide under normal operating conditions.

11. Toxicological Information

Carcinogenicity: This product is not carcinogenic according to the OSHA Hazard Communication Standard.

Acute Toxicity: On the skin can cause mild irritation.
On the eye can cause mild irritation.
Ingestion - can cause mild irritation.

12. Ecological Information

Ecological Toxicity: Not Determined

Environmental Fate: Not Determined



Safety Data Sheet

Product Name: E-Color/GH Combo Buffing Wheels

Revision Date: February 22, 2016

Issue Date: May 3, 2005

13. Disposal Considerations

Recommended Method of Disposal: Collect in containers, bags, or covered boxes. All disposal must comply with Federal, State, and local regulations.

EPA Hazardous Waste Number: Not a RCRA hazardous waste.

14. Transport Information

Handling Precautions: N/A

Storage Requirements: No special requirements

DOT Transportation Data (49 CFR 172.101):

Shipping Name: N/A
Shipping Symbols: N/A
Hazard Class: N/A
ID No.: N/A
Packing Group: N/A
Label: N/A
Special Provisions (172.102): N/A

Packaging Authorizations
a) **Exceptions:** N/A
b) **Non-bulk Packaging:** N/A
c) **Bulk Packaging:** N/A

Quantity Limitations
a) **Passenger, Aircraft, or Railcar:** N/A
b) **Cargo Aircraft Only:** N/A
Vessel Stowage Requirements
a) **Vessel Stowage:** N/A
b) **Other:** N/A

15. Regulatory Information

U.S. Federal Regulations:

TSCA Status: All Components of this product are listed on the TSCA Inventory

CERCLA Reportable Quantity: Unknown

SARA Title III:

Section 302 Extremely Hazardous Substances: None.

Section 311/312 Hazard Categories: Immediate (Acute), Chronic

Safety Data Sheet



Product Name: E-Color/GH Combo Buffing Wheels

Revision Date: February 22, 2016

Issue Date: May 3, 2005

16. Other Information

Prepared By: Schaffner Manufacturing Company, Inc

Disclaimer: The data and information contained herein are furnished for information only and are believed to be reliable. However, it is the user's responsibility to determine the suitability of Schaffner Manufacturing's products or any production methods for a particular purpose and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Schaffner Manufacturing's products. In light of the foregoing, Schaffner Manufacturing disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale of or use of Schaffner Manufacturing's products. Schaffner Manufacturing further disclaims any liability for consequential or incidental damages of any kind, including lost profits.