



Safety Data Sheet

Product Name: SS-5615 SC Spray Compound

Revision Date: August, 23rd 2018

Issue Date: November 15, 2013

1. Product and Company Identification

Product Name: SS-5615 EC

Product Description: Spray Compound

Company Address:

Schaffner Manufacturing Co. Inc.
21 Herron Ave.
Emsworth, PA 15202

Contact Information:

Telephone: 412-761-9902
Emergency Telephone: 412-761-9902
Internet: www.schaffnermfg.com

2. Hazards Identification

Signal Word: Warning

Primary Entry Routes: Skin contact, eye contact

Target Organs: Skin, eyes

Acute Effects

Inhalation: Irritation possible from prolonged contact

Eye: Irritation possible from prolonged contact

Skin: Irritation possible from prolonged contact

Ingestion:

Carcinogenicity: Based on Findings of the IARC (1997: Brown, et al), respirable crystalline silica is known to be a Human carcinogen.

Medical Conditions Aggravated by Long-Term Exposure: N/A

Chronic Effects: N/A



3. Composition - Information on Ingredients

| Component | CAS Number |
|--------------------|------------|
| Aluminum Oxide | 1344-28-1 |
| Crystalline Silica | 1317-95-9 |
| Hydrocarbon Wax | 64742-60-5 |
| Fatty Acid | 67701-03-5 |

| Ingredient | OSHA PEL | | ACGIH TLV | | NIOSHA REL | | IDLH |
|--------------------|-----------------------|------|-----------------------|------|------------|------|------|
| | TWA | STEL | TWA | STEL | TWA | STEL | |
| Aluminum Oxide | 10 mg/m ³ | N/E | 10 mg/m ³ | N/E | N/E | N/E | N/E |
| Crystalline Silica | 0.1 mg/m ³ | N/E | 0.1 mg/m ³ | N/E | N/E | N/E | N/E |
| Hydrocarbon Wax | N/E | N/E | N/E | N/E | N/E | N/E | N/E |
| Fatty Acid | 10 mg/m ³ | N/E | N/E | N/E | N/E | N/E | N/E |



Safety Data Sheet

Product Name: SS-5615 SC Spray Compound

Revision Date: August, 23rd 2018

Issue Date: November 15, 2013

4. First Aid Measures

Emergency and First Aid Procedures

Inhalation: Cough to clear throat. Seek Medical Attention

Eye Contact: Rinse with water for 15 minutes. Seek medical attention.

Skin Contact: Rinse with water.

Ingestion: Give water. Seek Medical attention.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Note to Physicians: None

Special Precautions/Procedures: It is recommended that safety glasses and dust mask be worn during operation.

5. Fire Fighting Measures

Flash Point: N/A

Flash Point Method: N/A

Burning Rate: N/A

Autoignition Temperature: N/A

LEL: N/A

UEL: N/A

Flammability Classification: N/A

Extinguishing Media: Water, CO₂, and Foam

Unusual Fire or Explosion Hazards: N/A

Hazardous Combustion Products: N/A

Fire-Fighting Instructions: Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.

Hazard Classification: Health: 1 Flammability: 1 Reactivity: 0



0 = Minimal 1=Slight 2=Moderate 3=Serious 4=Severe



Safety Data Sheet

Product Name: SS-5615 SC Spray Compound

Revision Date: August, 23rd 2018

Issue Date: November 15, 2013

6. Accidental Release Measures

Environmental Precautions: No special precautions required, disposal must be made in accordance with Federal, State and Local regulations.

Clean-up Methods: Absorb spill with inert material, then place in a chemical waste container for disposal.

7. Handling and Storage

Handling: Avoid contact with eyes, skin and clothing.

Storage: Store in a cool, dry area in a tightly closed container.

Incompatible Products: None known

8. Exposure Controls/ Personal Protection

Engineering Controls:

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Administrative Controls:

Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Protective Clothing/Equipment: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Safety Stations: Make emergency eyewash stations and washing facilities available in work area.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.



Safety Data Sheet

Product Name: SS-5615 SC Spray Compound

Revision Date: August, 23rd 2018

Issue Date: November 15, 2013

9. Physical and Chemical Properties

| | |
|---|---------------------------------------|
| Physical State: Liquid | Water Solubility: Soluble |
| Color: Varying | Other Solubility: N/A |
| Odor Threshold: N/A | Boiling Point: 212 °F (100 °C) |
| Vapor Pressure: N/A | Freezing/Melting Point: N/A |
| Vapor Density (Air=1): N/A | Viscosity: N/A |
| Formula Weight: none estab. | Refractive Index: N/A |
| Density: N/A | Surface Tension: N/A |
| Specific Gravity (H₂O=1, at 4 °C): 1.03 | % Volatile: N/A |
| pH: N/A | Evaporation Rate: N/A |

10. Stability and Reactivity

Stability: All Schaffner products are stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: N/A

Conditions to Avoid: N/A

Hazardous Decomposition Products: N/A

11. Toxicological Information

Carcinogenicity: Based on Findings of the IARC (1997: Brown, et al), respirable crystalline silica is known to be a Human carcinogen.

Acute Toxicity: On the skin can cause mild irritation.
On the eye can cause irritation.
Ingestion - can cause irritation.

12. Ecological Information

Ecological Toxicity: Not Determined

Environmental Fate: Not Determined

13. Disposal Considerations

Recommended Method of Disposal: Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

EPA Hazardous Waste Number: Not listed (40 CFR 261.33): N/A



Safety Data Sheet

Product Name: SS-5615 SC Spray Compound

Revision Date: August, 23rd 2018

Issue Date: November 15, 2013

14. Transport Information

Handling Precautions: N/A

Storage Requirements: No special requirements

DOT Transportation Data (49 CFR 172.101):

Shipping Name: N/A

Shipping Symbols: N/A

Hazard Class: N/A

ID No.: N/A

Packing Group: N/A

Label: N/A

Special Provisions

(172.102): N/A

Packaging Authorizations

a) Exceptions: N/A

b) Non-bulk Packaging:
N/A

c) Bulk Packaging: N/A

Quantity Limitations

a) Passenger, Aircraft, or Railcar:

N/A

b) Cargo Aircraft Only: N/A

Vessel Stowage Requirements

a) Vessel Stowage: N/A

b) Other: N/A

15. Regulatory Information

U.S. Federal Regulations:

TSCA Status: All Components of this product are listed on the TSCA Inventory

CERCLA Reportable Quantity: None

SARA Title III:

Section 302 Extremely Hazardous Substances: None.

Section 311/312 Hazard Categories: Immediate (Acute), Delayed (chronic)

California Proposition 65:

⚠️ WARNING: This product can expose you to Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.



Safety Data Sheet

Product Name: SS-5615 SC Spray Compound

Revision Date: August, 23rd 2018

Issue Date: November 15, 2013

16. Other Information

Prepared By: Schaffner Manufacturing Company, Inc

Disclaimer: The data and information contained herein are furnished for information only and are believed to be reliable. However, it is the user's responsibility to determine the suitability of Schaffner Manufacturing's products or any production methods for a particular purpose and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Schaffner Manufacturing's products. In light of the foregoing, Schaffner Manufacturing disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale of or use of Schaffner Manufacturing's products. Schaffner Manufacturing further disclaims any liability for consequential or incidental damages of any kind, including lost profits.