

Safety Data Sheet



Product Name: SS-5952 M Spray Compound

Revision Date: August, 23rd 2018

Issue Date: May 28, 2010

1. Product and Company Identification

Product Name: SS-5952 M

Product Description: Spray Compound

Company Address:

Schaffner Manufacturing Co. Inc.
21 Herron Ave.
Emsworth, PA 15202

Contact Information:

Telephone: 412-761-9902
Emergency Telephone: 412-761-9902
Internet: www.schaffnermfg.com

2. Hazards Identification

Signal Word: Warning

Primary Entry Routes: Skin contact, eye contact

Target Organs: Skin, eyes

Acute Effects

Inhalation: Irritation possible from prolonged contact

Eye: Irritation possible from prolonged contact

Skin: Irritation possible from prolonged contact

Ingestion:

Carcinogenicity: The raw materials in this product are not listed by NTP, IARC or regulated as a carcinogen by OSHA.

Medical Conditions Aggravated by Long-Term Exposure: N/A

Chronic Effects: N/A

3. Composition - Information on Ingredients

| Ingredient Name | CAS Number |
|-----------------|------------|
| Aluminum Oxide | 1344-28-1 |
| Fatty Acid | 67701-03-5 |
| Hydrocarbon Wax | 64742-60-5 |

| Ingredient | OSHA PEL | | ACGIH TLV | | NIOSH REL | | NIOSH IDLH |
|-----------------|----------------------|------|----------------------|------|-----------|------|------------|
| | TWA | STEL | TWA | STEL | TWA | STEL | |
| Aluminum Oxide | 10 mg/m ³ | N/E | 10 mg/m ³ | N/E | N/E | N/E | N/E |
| Fatty Acid | 10 mg/m ³ | N/E | N/E | N/E | N/E | N/E | N/E |
| Hydrocarbon Wax | N/E | N/E | N/E | N/E | N/E | N/E | N/E |

Safety Data Sheet



Product Name: SS-5952 M Spray Compound

Revision Date: August, 23rd 2018

Issue Date: May 28, 2010

4. First Aid Measures

Emergency and First Aid Procedures

Inhalation: Cough to clear throat. Seek Medical Attention

Eye Contact: Rinse with water for 15 minutes. Seek medical attention.

Skin Contact: Rinse with water.

Ingestion: Give water. Seek Medical attention.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Note to Physicians: None

Special Precautions/Procedures: It is recommended that safety glasses and dust mask be worn during operation

5. Fire Fighting Measures

Flash Point: N/A

Flash Point Method: N/A

Burning Rate: N/A

Autoignition Temperature: N/A

LEL: N/A

UEL: N/A

Flammability Classification: N/A

Extinguishing Media: Water, carbon dioxide, and foam

Unusual Fire or Explosion Hazards: N/A

Hazardous Combustion Products: N/A

Fire-Fighting Instructions: Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.

Hazard Classification: Health: 1 Flammability: 1 Reactivity: 0



0 = Minimal 1=Slight 2=Moderate 3=Serious 4=Severe

Safety Data Sheet



Product Name: SS-5952 M Spray Compound

Revision Date: August, 23rd 2018

Issue Date: May 28, 2010

6. Accidental Release Measures

Environmental Precautions: No special precautions required, disposal must be made in accordance with Federal, State and Local regulations.

Clean-up Methods: Vacuum or sweep spilled material and place waste material in approved container.

7. Handling and Storage

Handling: Protective gloves are recommended for prolonged handling.

Storage: Store in a cool, dry area.

Incompatible Products: Glycerol, Oxygen DiFlouride and strong oxidizers.

8. Exposure Controls/ Personal Protection

Engineering Controls:

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Administrative Controls:

Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Protective Clothing/Equipment: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Safety Stations: Make emergency eyewash stations and washing facilities available in work area.

Safety Data Sheet



Product Name: SS-5952 M Spray Compound

Revision Date: August, 23rd 2018

Issue Date: May 28, 2010

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

9. Physical and Chemical Properties

Physical State: Liquid

Appearance and Odor: Light Yellow

Odor Threshold: N/A

Vapor Pressure: N/A

Vapor Density (Air=1): N/A

Formula Weight: none estab.

Density: N/A

Specific Gravity (H₂O=1, at 4 °C): G.T. 1.35

pH: N/A

Water Solubility: Soluble

Other Solubilities: N/A

Boiling Point: 212 °F (100°C)

Freezing/Melting Point: Binder - Greater than 130°F, (54°C)

Viscosity: 15-25 Kcps

Refractive Index: N/A

Surface Tension: N/A

% Volatile: N/A

Evaporation Rate: N/A

10. Stability and Reactivity

Stability: All Schaffner products are stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: N/A

Conditions to Avoid: N/A

Hazardous Decomposition Products: N/A

11. Toxicological Information

Carcinogenicity: The raw materials in this product are not listed by NTP, IARC or regulated as a carcinogen by OSHA.

Acute Toxicity: On the skin can cause mild irritation.
On the eye can cause mild irritation.
Ingestion - can cause mild irritation.

Safety Data Sheet



Product Name: SS-5952 M Spray Compound

Revision Date: August, 23rd 2018

Issue Date: May 28, 2010

12. Ecological Information

Ecological Toxicity: Not Determined

Environmental Fate: Not Determined

13. Disposal Considerations

Recommended Method of Disposal: Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

EPA Hazardous Waste Number: Not listed (40 CFR 261.33): N/A

14. Transport Information

Handling Precautions: N/A

Storage Requirements: No special requirements

DOT Transportation Data (49 CFR 172.101):

Shipping Name: N/A
Shipping Symbols: N/A
Hazard Class: N/A
ID No.: N/A
Packing Group: N/A
Label: N/A
Special Provisions (172.102): N/A

Packaging Authorizations
a) Exceptions: N/A
b) Non-bulk Packaging: N/A
c) Bulk Packaging: N/A

Quantity Limitations
a) Passenger, Aircraft, or Railcar: N/A
b) Cargo Aircraft Only: N/A

Vessel Stowage Requirements
a) Vessel Stowage: N/A
b) Other: N/A

Safety Data Sheet



Product Name: SS-5952 M Spray Compound

Revision Date: August, 23rd 2018

Issue Date: May 28, 2010

15. Regulatory Information

U.S. Federal Regulations:

TSCA Status: All Components of this product are listed on the TSCA Inventory

CERCLA Reportable Quantity: Unknown

SARA Title III:

Section 302 Extremely Hazardous Substances: None.

Section 311/312 Hazard Categories: Immediate (Acute), Chronic

California Proposition 65:

⚠️ WARNING: This product can expose you to Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

16. Other Information

Prepared By: Schaffner Manufacturing Company, Inc

Disclaimer: The data and information contained herein are furnished for information only and are believed to be reliable. However, it is the user's responsibility to determine the suitability of Schaffner Manufacturing's products or any production methods for a particular purpose and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Schaffner Manufacturing's products. In light of the foregoing, Schaffner Manufacturing disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale of or use of Schaffner Manufacturing's products. Schaffner Manufacturing further disclaims any liability for consequential or incidental damages of any kind, including lost profits.