



## Safety Data Sheet

**Product Name:** X2154 Treated  
**Buffing Wheel**  
**Revision Date:** May 25, 2016  
**Issue Date:** April 24, 2015

### 1. Product and Company Identification

**Product Name:** Treated Buffing Wheel  
**Company Address:**  
Schaffner Manufacturing Co. Inc.  
21 Herron Ave.  
Emsworth, Pa. 15202

**Product Description:** Buffing Wheels  
**Contact Information:**  
Telephone: 412-761-9902  
Emergency Telephone: 412-761-9902  
Internet: [www.schaffnermfg.com](http://www.schaffnermfg.com)

### 2. Hazards Identification

**Signal Word:** Warning

**Primary Entry Routes:** Skin contact, eye contact

**Target Organs:** Skin, eyes

**Acute Effects**

**Inhalation:** Irritation possible from prolonged contact

**Eye:** Irritation possible from prolonged contact

**Skin:** Irritation possible from prolonged contact

**Ingestion:**

**Carcinogenicity:** IARC, NTP, and OSHA do not list this as carcinogenic.

**Medical Conditions Aggravated by Long-Term Exposure:** N/A

**Chronic Effects:** N/A

### 3. Composition - Information on Ingredients

Ingredient Name	CAS Number
Acrylic Copolymer	9011-14-7
Cotton/Sisal Fibers	N/A

# Safety Data Sheet



**Product Name:** X2154 Treated  
**Buffing Wheel**  
**Revision Date:** May 25, 2016  
**Issue Date:** April 24, 2015

Ingredient	OSHA PEL		ACGIH TLV		NIOSH REL		NIOSH IDLH
	TWA	STEL	TWA	STEL	TWA	STEL	
Acrylic Copolymer	10 mg/m <sup>3</sup>	none estab	10 mg/m <sup>3</sup>	none estab.	none estab.	none estab.	none estab.
Cotton/Sisal Fibers	none estab.	none estab.	none estab.	none estab.	none estab.	none estab.	none estab.

## 4. First Aid Measures

### Emergency and First Aid Procedures

**Inhalation:** Cough to clear throat. Seek Medical Attention

**Eye Contact:** Rinse with water for 15 minutes. Seek medical attention.

**Skin Contact:** Rinse with water.

**Ingestion:** Give water. Seek Medical attention.

*After first aid, get appropriate in-plant, paramedic, or community medical support.*

**Note to Physicians:** None

**Special Precautions/Procedures:** It is recommended that safety glasses and dust mask be worn during operation.

## 5. Fire Fighting Measures

**Flash Point:** Cotton Fiber ~ 250F

**Flash Point Method:** N/A

**Burning Rate:** N/A

**Autoignition Temperature:** N/A

**LEL:** N/A

**UEL:** N/A

**Flammability Classification:** N/A

**Extinguishing Media:** Water, carbon dioxide, and Foam

**Unusual Fire or Explosion Hazards:** N/A

**Hazardous Combustion Products:** N/A

**Fire-Fighting Instructions:** Do not release runoff from fire control methods to sewers or waterways.

**Fire-Fighting Equipment:** Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

## 6. Accidental Release Measures

**Environmental Precautions:** No special precautions required, disposal must be made in



## Safety Data Sheet

**Product Name:** X2154 Treated  
**Buffing Wheel**  
**Revision Date:** May 25, 2016  
**Issue Date:** April 24, 2015

accordance with Federal, State and Local regulations.

**Clean-up Methods:** Clean up and dispose of in accordance with applicable laws.  
container.

### 7. Handling and Storage

**Handling:** Protective gloves are recommended for prolonged handling.

**Storage:** Store in a cool, dry area.

**Incompatible Products:** N/A

### 8. Exposure Controls/ Personal Protection

**Engineering Controls:**

**Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

**Administrative Controls:**

**Respiratory Protection:** Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

**Protective Clothing/Equipment:** Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

**Safety Stations:** Make emergency eyewash stations and washing facilities available in work area.

**Contaminated Equipment:** Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

**Comments:** Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.



## Safety Data Sheet

**Product Name:** X2154 Treated  
**Buffing Wheel**  
**Revision Date:** May 25, 2016  
**Issue Date:** April 24, 2015

### 9. Physical and Chemical Properties

<b>Physical State:</b> Solid	<b>Water Solubility:</b> N/A
<b>Appearance and Odor:</b> Varying	<b>Other Solubility:</b> N/A
<b>Odor Threshold:</b> N/A	<b>Boiling Point:</b> N/A
<b>Vapor Pressure:</b> N/A	<b>Freezing/Melting Point:</b> N/A
<b>Vapor Density (Air=1):</b> N/A	<b>Viscosity:</b> N/A
<b>Formula Weight:</b> none estab.	<b>Refractive Index:</b> N/A
<b>Density:</b> N/A	<b>Surface Tension:</b> N/A
<b>Specific Gravity (H<sub>2</sub>O=1, at 4 °C):</b> N/A	<b>% Volatile:</b> N/A
<b>pH:</b> N/A	<b>Evaporation Rate:</b> N/A

### 10. Stability and Reactivity

**Stability:** All Schaffner Abrasives wheels are stable at room temperature in closed containers under normal storage

And handling conditions

**Polymerization:** Hazardous polymerization cannot occur.

**Chemical Incompatibilities:** N/A

**Conditions to Avoid:** N/A

**Hazardous Decomposition Products:** N/A

### 11. Toxicological Information

**Carcinogenicity:** This product is not carcinogenic according to the OSHA Hazard Communication Standard.

**Acute Toxicity:** On the skin can cause mild irritation.  
On the eye can cause mild irritation.  
Ingestion - can cause mild irritation.

### 12. Ecological Information

**Ecological Toxicity:** Not Determined

**Environmental Fate:** Not Determined



## Safety Data Sheet

**Product Name:** X2154 Treated  
**Buffing Wheel**  
**Revision Date:** May 25, 2016  
**Issue Date:** April 24, 2015

### 13. Disposal Considerations

**Recommended Method of Disposal:** Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

**EPA Hazardous Waste Number:** Not listed (40 CFR 261.33): N/A

### 14. Transport Information

**Handling Precautions:** N/A

**Storage Requirements:** No special requirements

#### DOT Transportation Data (49 CFR 172.101):

**Shipping Name:** N/A  
**Shipping Symbols:** N/A  
**Hazard Class:** N/A  
**ID No.:** N/A  
**Packing Group:** N/A  
**Label:** N/A  
**Special Provisions**  
**(172.102):** N/A

**Packaging Authorizations**  
a) **Exceptions:** N/A  
b) **Non-bulk Packaging:**  
N/A  
c) **Bulk Packaging:** N/A

**Quantity Limitations**  
a) **Passenger, Aircraft, or Railcar:**  
N/A  
b) **Cargo Aircraft Only:** N/A

**Vessel Stowage Requirements**  
a) **Vessel Stowage:** N/A  
b) **Other:** N/A

### 15. Regulatory Information

#### U.S. Federal Regulations:

**TSCA Status:** All Components of this product are listed on the TSCA Inventory

**CERCLA Reportable Quantity:** Unknown

#### SARA Title III:

**Section 302 Extremely Hazardous Substances:** None.

**Section 311/312 Hazard Categories:** Immediate (Acute), Chronic



## Safety Data Sheet

**Product Name:** X2154 Treated  
**Buffing Wheel**  
**Revision Date:** May 25, 2016  
**Issue Date:** April 24, 2015

### 16. Other Information

**HMIS: Health: 1**

**Flammability: 1**

**Reactivity: 0**

**Prepared By:** Schaffner Manufacturing Company, Inc

**Disclaimer:** The data and information contained herein are furnished for information only and are believed to be reliable. However, it is the user's responsibility to determine the suitability of Schaffner Manufacturing's products or any production methods for a particular purpose and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Schaffner Manufacturing's products. In light of the foregoing, Schaffner Manufacturing disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale of or use of Schaffner Manufacturing's products. Schaffner Manufacturing further disclaims any liability for consequential or incidental damages of any kind, including lost profits.